

DB/DA Bi-Metal Dial Thermometers

Fixed Position or Any Angle

100mm (4 inch) Ø 304 Stainless Steel crimped case dial with a 316 Stainless Steel probe. The dial has a white background, black markings, black aluminium pointer and shatterproof glass. The dial thermometers are simple in construction, yet rugged and reliable, offering a fast response with an accuracy conforming to C1.1 EN 13190:2001 and over-range of 125% FSD. Supplied as standard with a 1/2" BSP tapered compression fitting (other threads available on request).

Available as fixed position (bottom or back entry) or any-angle.					
Technical Details					
Dial	100mm (4"), white background, black markings				
Pointer	Aluminium, black				
Case	304 Stainless Steel, crimped, IP65				
Window	Shatterproof glass				
Stem	6mm OD (316 Stainless Steel)				
Fitting	1/2" BSPT Stainless Steel Adjustable Compression Fitting (sliding)				
Accuracy	As per C1.1 EN 13190:2001				
Over-Range	125% FSD				





Zero Reset External, provided






Fixed Position (Bottom Entry)

Fixed Position (Back Entry)

Any Angle

Tixed Tosition (Bottom Entry)		Tixed Tosition (Back Entry)		Ally Aligic			
style	bottom/back entry	stem Ø	stem length *	temperature range	order code		
Fixed Position	Bottom Entry	6.0mm	200mm	-40°C to +60°C	DB06/060B		
Fixed Position	Bottom Entry	6.0mm	200mm	0°C to +120°C	DB06/120B		
Fixed Position	Bottom Entry	6.0mm	200mm	-50°C to +150°C	DB06/150B		
Fixed Position	Bottom Entry	6.0mm	200mm	0°C to +200°C	DB06/200B		
Fixed Position	Bottom Entry	6.0mm	200mm	0°C to +300°C	DB06/300B		
Fixed Position	Bottom Entry	6.0mm	200mm	0°C to +400°C	DB06/400B		
Fixed Position	Bottom Entry	6.0mm	200mm	0°C to +500°C	DB06/500B		
Fixed Position	Back Entry	6.0mm	200mm	-40°C to +60°C	DB06/060R		
Fixed Position	Back Entry	6.0mm	200mm	0°C to +120°C	DB06/120R		
Fixed Position	Back Entry	6.0mm	200mm	-50°C to +150°C	DB06/150R		
Fixed Position	Back Entry	6.0mm	200mm	0°C to +200°C	DB06/200R		
Fixed Position	Back Entry	6.0mm	200mm	0°C to +300°C	DB06/300R		
Fixed Position	Back Entry	6.0mm	200mm	0°C to +400°C	DB06/400R		
Fixed Position	Back Entry	6.0mm	200mm	0°C to +500°C	DB06/500R		
Any Angle	Adjustable	6.0mm	200mm	-40°C to +60°C	DA06/060		
Any Angle	Adjustable	6.0mm	200mm	0°C to +120°C	DA06/120		
Any Angle	Adjustable	6.0mm	200mm	-50°C to +150°C	DA06/150		
Any Angle	Adjustable	6.0mm	200mm	0°C to +200°C	DA06/200		
Any Angle	Adjustable	6.0mm	200mm	0°C to +300°C	DA06/300		
Any Angle	Adjustable	6.0mm	200mm	0°C to +400°C	DA06/400		
Any Angle	Adjustable	6.0mm	200mm	0°C to +500°C	DA06/500		
* Stem length = tip to underside of thread							



DDV Bi-Metal Dial Thermometer with Thermowell (HVAC)

Low-cost Stainless Steel temperature gauges, commonly used for heating and ventilation, hot water boilers and solar power systems.

- · 63mm and 100mm diameter dials
- 0-60°C, 0-120°C and 0-160°C temperature ranges

Contact sales for further information





